



RAVENOL RNV SAE 5W-30



1L | 1111114-001
4L | 1111114-004
5L | 1111114-005
10L | 1111114-010
20L | 1111114-020
20L | 1111114-B20
60L | 1111114-060
208L | 1111114-208
1000L | 1111114-700

Kategorie: Passenger car motor oil

Artikelnummer: 1111114

Viscosity: 5W-30

Specifications: ACEA C3

Oil type: Synthetic

Approvals: MB -Freigabe 226.52, Renault RN17

Recommendations: Fiat 9.55535-S3, MB 229.51, MB 229.52, Renault RN0700, Renault RN0710

Application: Passenger car

Technology: CleanSynto

RAVENOL RNV SAE 5W-30 is a synthetic low-friction motor oil with CleanSynto® technology for passenger car petrol and diesel engines based on the latest additive technology with selected base oils. It was specially developed for Renault and Dacia engines.

RAVENOL RNV SAE 5W-30 is suitable for use in petrol and diesel engines with and without a particle filter and exhaust gas catalytic converter and in engines according to the latest EURO 6d-Temp standard.

The viscosity range SAE 5W-30 ensures a reliable cold start at low outside temperatures and full lubricity at high operating temperatures. Frictional losses and wear are reduced.

By significantly reducing fuel consumption, **RAVENOL RNV SAE 5W-30** helps to protect the environment by reducing emissions.

Extended oil change intervals according to the manufacturer's instructions.

Application instructions

RAVENOL RNV SAE 5W-30 is suitable for all petrol engines, diesel engines without DPF (Diesel Particulate Filter), diesel engines with DPF from EURO 6d-Temp by RENAULT and Dacia as well as for diesel engines with DPF, if an engine oil according to ACEA C3 is required.

RAVENOL RNV SAE 5W-30 can be used universally in all petrol and diesel engines with and without turbocharging, except RS /Alpine.

RAVENOL RNV SAE 5W-30 can also be used for the latest EURO 6d engines.

The Renault specification RN17 replaces the specification RN0700 and RN0710.

The oil change intervals according to the manufacturer's instructions must be observed.

Characteristics

- Low content of ash-forming components (sulfate ash, phosphorus and sulfur).
- Specific additive technology for optimal lubrication.
- Extremely high aging resistance, durability and robustness.
- Excellent cleaning properties
- Fuel savings

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	0,76	DIN 51575
tbn	mg KOH/g	8,7	ASTM D2896
Viscosity at 100 °C	mm ² /s	12,0	DIN 51562-1
Viscosity at 40 °C	mm ² /s	64,0	DIN 51562-1
Viscosity Index VI		187	DIN ISO 2909
CCS Viscosity at -30 °C	mPa*s	5576	ASTM D5293
Density at 20 °C	kg/m ³	845,0	EN ISO 12185
Flashpoint	°C	240	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	3,7	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	22.370	ASTM D4684
Noack Volatility	% M/M	7,6	ASTM D5800
Pourpoint	°C	-36	DIN ISO 3016