



RAVENOL HPS SAE 5W-30



1L | 1111117-001
4L | 1111117-004
5L | 1111117-005
10L | 1111117-010
20L | 1111117-020
20L | 1111117-B20
60L | 1111117-060
60L | 1111117-D60
208L | 1111117-208
208L | 1111117-D28
1000L | 1111117-700

Kategorie: Passenger car motor oil

Artikelnummer: 1111117

Viscosity: 5W-30

Specifications: ACEA A3/B4, API CF, API SL

Oil type: Semi-synthetic

Recommendations: BMW Longlife-98, MB 229.3, VW 502 00, VW 505 00

Application: Passenger car

Technology: CleanSynto

RAVENOL HPS SAE 5W-30 is modern high performance low friction semi synthetic hydrocrack hypersynth multigrade motor oil with CleanSynto® technology, formulated with PAO (Polyalphaolefines), for passenger car gasoline and diesel engines, with and without turbocharging and direct injection.

RAVENOL HPS SAE 5W-30 achieves a high viscosity index through its formulation with special base oils. The excellent cold start behaviour provides an optimum lubricating safety during the cold run phase.

Because of a considerable fuel saving **RAVENOL HPS SAE 5W-30** contributes to protect the environment by reducing the emissions.

RAVENOL HPS SAE 5W-30 minimizes friction, wear and fuel consumption with excellent cold start characteristics.

Suitable for extended oil change intervals where recommended by manufacturer.

Application instructions

RAVENOL HPS SAE 5W-30 is low friction motor oil, which is suitable for performance motors. It is recommended for all modern passenger car gasoline and diesel engines, including turbo versions and for direct injection motors and also recommended for all operation conditions.

Characteristics

- Fuel economy in part and full power operation.
- Very stable and excellent viscosity behaviour.
- Excellent shear stability.
- Excellent cold starting characteristics.
- A safe lubricant film at high operating temperatures.
- Excellent detergent- and dispersant characteristics.
- High wear and corrosion protection, high oxidation stability.
- Prevention of sludge formation.
- Extended lifetime because of oxidation stability.
- Suitable for catalysts.

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	1,18	DIN 51575
tbn	mg KOH/g	11,0	ASTM D2896
Viscosity at 100 °C	mm ² /s	12,15	DIN 51562-1
Viscosity at 40 °C	mm ² /s	70,9	DIN 51562-1
Viscosity Index VI		170	DIN ISO 2909
CCS Viscosity at -30 °C	mPa*s	6140	ASTM D5293
Density at 20 °C	kg/m ³	850,0	EN ISO 12185
Flashpoint	°C	232	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	3,71	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	20.800	ASTM D4684
Noack Volatility	% M/M	8,9	ASTM D5800
Pourpoint	°C	-39	DIN ISO 3016