



RAVENOL SHL SAE 0W-40



Kategorie: Passenger car motor oil

Artikelnummer: 1111127

Viscosity: 0W-40

Specifications: ACEA A3/B4, API SN

Oil type: Synthetic

Approvals: API SN, MB -Freigabe 229.5, Porsche A40, Renault RN0710, VW 502 00, VW 505 00

Recommendations: BMW Longlife-01, Ford WSS-M2C937-A, Renault RN0700

Application: Passenger car

Technology: CleanSynto

RAVENOL SHL SAE 0W-40 is a HC (Hydrocrack) and PAO (Polyalphaolefin) based, synthetic motoroil with CleanSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

RAVENOL SHL SAE 0W-40 provides a safe layer of lubrication even at very high operating temperatures and protects from corrosion and loss of oil through oxidation or coking. The excellent cold start behavior ensures optimum lubrication safety during the cold running phase.

By significantly reducing fuel consumption, **RAVENOL SHL SAE 0W-40** helps to protect the environment by reducing emissions.

RAVENOL SHL SAE 0W-40 minimizes friction, wear and fuel consumption with excellent cold start characteristics.

Extended oil change intervals according to the manufacturer's instructions.

Application instructions

RAVENOL SHL SAE 0W-40 guarantees operational safety in all driving conditions such as extreme stop-and-go traffic and high-speed highway driving.

RAVENOL SHL SAE 0W-40 is universal fuel-efficient synthetic engine oil suitable for petrol and diesel engines, with or without turbocharger, in cars and vans with the specified quality classifications.

Characteristics

- Excellent cold starting behavior
- Fuel savings for part and full load
- A very stable and excellent viscosity behavior
- Good shear stability
- A safe lubricant film at very high operating temperatures
- Excellent detergent and dispersant properties
- A broad protection against wear, corrosion and foaming
- Excellent aging stability

1L | 1111127-001

4L | 1111127-004

5L | 1111127-005

10L | 1111127-010

20L | 1111127-020

20L | 1111127-B20

60L | 1111127-060

60L | 1111127-D60

208L | 1111127-208

208L | 1111127-D28

- Low evaporation loss
- Excellent engine cleanliness

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		braun	VISUELL
Sulphated Ash	%wt.	1,15	DIN 51575
tbn	mg KOH/g	10,46	ASTM D2896
Viscosity at 100 °C	mm ² /s	13,46	DIN 51562-1
Viscosity at 40 °C	mm ² /s	75,0	DIN 51562-1
Viscosity Index VI		185	DIN ISO 2909
CCS Viscosity at -35 °C	mPa*s	5950	ASTM D5293
Density at 20 °C	kg/m ³	842,0	EN ISO 12185
Flashpoint	°C	228	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	3,84	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -40 °C	mPa*s	28.600	ASTM D4684
Noack Volatility	% M/M	9,4	ASTM D5800
Pourpoint	°C	-45	DIN ISO 3016