



RAVENOL Turbo-C HD-C SAE 15W-40



1L | 1113103-001

4L | 1113103-004

5L | 1113103-005

10L | 1113103-010

20L | 1113103-020

20L | 1113103-B20

60L | 1113103-060

60L | 1113103-D60

208L | 1113103-208

208L | 1113103-D28

1000L | 1113103-700

Kategorie: Passenger car motor oil

Artikelnummer: 1113103

Viscosity: 15W-40

Specifications: ACEA A3/B4, ACEA E2, API CF, API CF-4, API SL

Oil type: Mineral

Approvals: API SL

Recommendations: Allison C4, Caterpillar TO-2, Mack EO-L, MAN 271, MAN M 3275-1, MB 229.1, MTU Typ 2, VOLVO VDS, VW 505 00, VW 501 01, ZF TE-ML 07C

Application: Passenger car

RAVENOL Turbo-C HD-C SAE 15W-40 is high quality multi-grade engine oil for passenger cars and trucks with diesel engines with or without turbo charger which has been adapted to the ever-growing demands.

It is also suitable for use gasoline (petrol) engines. It has an excellent lubricating film adhesion and very good shear stability and an excellent cleaning power and high resistance to aging.

Application instructions

RAVENOL Turbo-C HD-C SAE 15W-40 is perfectly suited as all-season motor oil for the mixed fleet. It can be used in the commercial vehicle sector for operation and extended oil change interval (up to 45,000 kilometres are possible) according to manufacturer's specifications.

Characteristics

- An excellent shear stability
- Very good cold start characteristics
- A very high oxidation stability
- Avoids the formation of coking and accumulation of mud (black sludge)
- A very stable and excellent viscosity behaviour
- Suitable for catalysts
- Convincing detergent and dispersant attributes
- High security reserves even under limited lubrication conditions

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	1,1	DIN 51575
tn	mg KOH/g	8,5	ASTM D2896
Viscosity at 100 °C	mm ² /s	14,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	107,2	DIN 51562-1
Viscosity Index VI		137	DIN ISO 2909
Density at 20 °C	kg/m ³	873,0	EN ISO 12185
Flashpoint	°C	244	DIN EN ISO 2592
Pourpoint	°C	-39	DIN ISO 3016