



# RAVENOL Regular 30

**Kategorie:** Oltimer engine oil (Classic products)

**Artikelnummer:** 1113302

**Viscosity:** 30

**Specifications:** API SA

**Oil type:** Mineral

**Application:** Hobby and garden, Passenger car



RAVENOL Motorenoel SAE 30 W Regular is a non-alloyed engine oil, it is manufactured using carefully selected pure mineral raffinates. It provides oxidation stability, it is non-foaming and also has excellent viscosity-temperature characteristics. Thanks to its low setting point, this oil can be used in both low and high temperatures and guarantees perfect lubrication.

## Application instructions

RAVENOL Motorenoel SAE 30 W Regular SA is used in passenger car petrol and diesel engines where the API specification SA is required.

20L | 1113302-020

20L | 1113302-B20

60L | 1113302-060

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		braun	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	11,0	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	92,0	DIN 51562-1
Viscosity Index VI		105	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	882,0	EN ISO 12185
Flashpoint	°C	245	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016