



# RAVENOL Spezial Diesel SAE 15W-40



1L | 1113311-001  
4L | 1113311-004  
5L | 1113311-005  
20L | 1113311-020  
20L | 1113311-B20  
60L | 1113311-060  
208L | 1113311-208  
1000L | 1113311-700

**Kategorie:** Truck engine oil

**Artikelnummer:** 1113311

**Viscosity:** 15W-40

**Specifications:** ACEA B2, API CD

**Oil type:** Mineral

**Recommendations:** CCMC G4, MB 227.1, MIL -L-2104 D, MIL -L-46152 B

**Application:** Hobby and garden, Passenger car, Truck, Agricultural machinery

**RAVENOL Spezial Diesel SAE 15W-40** is excellent multi-grade special engine oil which can be used in passenger cars as well as trucks. It fulfils the requirements of modern Diesel engines with or without supercharging. The favorable viscosity range ensures year-round high lubricity under different operating conditions.

## Application instructions

**RAVENOL Spezial Diesel SAE 15W-40** can be used according to the manufacturer specification for Dieselenines.

## Characteristics

- A good shear stability
- A high oxidation stability
- An excellent viscosity temperature behaviour
- Convincing detergent and dispersant attributes
- High security reserves even under limited lubrication conditions
- Very good cold start attributes
- Avoids the formation of accumulations of mud (black sludge)
- No problems with the use in catalyst vehicles

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	0,9	DIN 51575
tn	mg KOH/g	7,1	ASTM D2896
Viscosity at 100 °C	mm <sup>2</sup> /s	14,1	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	106,1	DIN 51562-1
Viscosity Index VI		135	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	865,0	EN ISO 12185
Flashpoint	°C	240	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016