



# RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40



1L | 1115100-001  
5L | 1115100-005  
20L | 1115100-020  
60L | 1115100-060  
60L | 1115100-D60  
208L | 1115100-208

**Kategorie:** Passenger car motor oil

**Artikelnummer:** 1115100

**Viscosity:** 5W-40

**Specifications:** ACEA A3/B4, API SN Plus, API SP

**Oil type:** Synthetic

**Recommendations:** BMW Longlife-01, MB 229.5, Opel/GM -LL-B-025, Porsche A40, Renault RN0700, Renault RN0710, VW 502 00, VW 505 00

**Application:** Passenger car

The synthetic motor oil **RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40** is a new development with a unique formula specifically for high mileage vehicles of approx. 100,000 km and more.

**RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40** is particularly recommended for vehicles with high mileage petrol and diesel engines with and without turbocharge and direct injection.

The extremely conditioning and cleaning agents in **RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40** revitalise critical engine parts and particularly protect gaskets. This can extend the life, particularly in older vehicles with high mileage.

**RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40** features outstanding lubrication and excellent shear stability, and the added conditioners simultaneously reduce oil consumption and protect from sludge and wear.

## Application instructions

**RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40** is perfectly suited for year-round use in high mileage petrol and diesel engines with 100,000 km and more, and promotes low oil consumption. A very clean engine is guaranteed.

**RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40** extends the life of the engine in older vehicles by reducing oil consumption and protecting from sludge and wear. A very clean engine is guaranteed.

## Characteristics

- High wear protection
- Fuel saving because of easy running characteristics
- Outstanding detergent and dispersant properties prevent sludge
- High oxidation stability for a long life
- Brilliant cold cranking behaviour
- Excellent viscosity-temperature behaviour
- Low vaporisation characteristics, therefore reduced oil consumption
- Suitable for catalytic converters

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		braun	VISUELL
Sulphated Ash	%wt.	1,19	DIN 51575
tbn	mg KOH/g	12,0	ASTM D2896
Viscosity at 100 °C	mm <sup>2</sup> /s	13,3	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	78,2	DIN 51562-1
Viscosity Index VI		173	DIN ISO 2909
CCS Viscosity at -30 °C	mPa*s	5480	ASTM D5293
Density at 20 °C	kg/m <sup>3</sup>	847,0	EN ISO 12185
Flashpoint	°C	240	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	3,91	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	25.000	ASTM D4684
Noack Volatility	% M/M	8,7	ASTM D5800
Pourpoint	°C	-42	DIN ISO 3016