



RAVENOL SVP Stand. Viscos. Perform. Oil SAE 15W-40

Kategorie: Passenger car motor oil

Artikelnummer: 1117100

Viscosity: 15W-40

Specifications: ACEA A3/B4, API CF, API SJ

Oil type: Mineral

Recommendations: MAN 271, MB 229.1, VW 505 00, ZF TE-ML 07C

Application: Passenger car



1L | 1117100-001

4L | 1117100-004

5L | 1117100-005

10L | 1117100-010

20L | 1117100-020

20L | 1117100-B20

60L | 1117100-060

208L | 1117100-208

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 is particularly recommended for vehicles with high mileage petrol and diesel engines with and without turbocharge and direct injection. The mineral motor oil **RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40** is a new development with a unique formula specifically for high mileage vehicles of approx. 100,000 km and more.

The extremely conditioning and cleaning agents in **RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40** revitalise critical engine parts and particularly protect gaskets. This can extend the life, particularly in older vehicles with high mileage.

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 features outstanding lubrication and excellent shear stability, and the added conditioners simultaneously reduce oil consumption and protect from sludge and wear.

Application instructions

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 is perfectly suited for year-round use in high mileage petrol and diesel engines with 100,000 km and more, and promotes low oil consumption. A very clean engine is guaranteed.

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 extends the life of the engine in older vehicles by reducing oil consumption and protecting from sludge and wear. A very clean engine is guaranteed.

Characteristics

- High wear protection, important for large mileages and inadequate oil changes
- Outstanding detergent and dispersant properties prevent sludge
- High oxidation stability for a long life
- Brilliant cold cranking behaviour through special additives
- Excellent viscosity-temperature behaviour
- Low vaporisation characteristics, therefore reduced oil consumption
- Suitable for catalytic converters

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash		1,1	DIN 51575
tdn		8,9	ASTM D2896
Viscosity at 100 °C		14,4	DIN 51562-1
Viscosity at 40 °C		107,2	DIN 51562-1
Viscosity Index VI		137	DIN ISO 2909
Density at 20 °C		873	EN ISO 12185
Flashpoint (CC)		240	DIN EN ISO 2592
Pourpoint		-36	DIN ISO 3016