



# RAVENOL Oldtimer Regular SAE 30 API SA

**Kategorie:** Oldtimer engine oil (Classic products)

**Artikelnummer:** 1118103

**Viscosity:** 30

**Specifications:** API SA

**Oil type:** Mineral

**Application:** Oldtimer



**1L | 1118103-001**

**5L | 1118103-005**

**60L | 1118103-060**

With their unique formulation, **RAVENOL Classic 1 Engine Oils** extend the service life of engines in older vehicles by offering protection against sludge formation and wear and tear. By minimising friction, fuel consumption is also reduced.

**RAVENOL Oldtimer Regular SAE 30 API SA** is a non-alloyed single grade engine oil for use in classic vehicles without an oil filter. It is manufactured using carefully selected pure mineral raffinates. It provides oxidation stability, it is non-foaming and also has excellent viscosity-temperature characteristics. Thanks to its low setting point, this oil can be used in both low and high temperatures and guarantees perfect lubrication. It is suitable for use in most petrol engines / classic vehicles built before 1930.

**RAVENOL Oldtimer Regular SAE 30 API SA** is especially recommended for old pre-war engines, where sludge should settle in the oil pan as there is no oil filter. The oil does not contain any active ingredients which can remove the sludge or deposits and keep them in suspension. Using this oil in modern engines can lead to defective performance or cause damage.

## Application instructions

**RAVENOL Oldtimer Regular SAE 30 API SA** is designed for use in the engines of vehicles which were built prior to 1930, where the API specification SA is required. Adhere to oil change intervals specified in the manufacturer's instructions.

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	11,2	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	103,1	DIN 51562-1
Viscosity Index VI		92	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	877,0	EN ISO 12185
Flashpoint	°C	266	DIN EN ISO 2592
Pourpoint	°C	-12	DIN ISO 3016