



RAVENOL Super Low Emission Truck SAE 15W-40



20L | 1123216-020
20L | 1123216-B20
60L | 1123216-060
60L | 1123216-D60
208L | 1123216-208
208L | 1123216-D28

Kategorie: Truck engine oil

Artikelnummer: 1123216

Viscosity: 15W-40

Specifications: ACEA E11, ACEA E7, ACEA E9, API CK-4, API SN

Oil type: Mineral

Approvals: DTFR 15C100, Mack EOS-4.5, Renault VI RLD-3, VOLVO VDS-4.5

Recommendations: Caterpillar ECF-3, Cummins CES 20081, Cummins CES 20086, Detroit Diesel Corporation (DDC) DFS93K218, Detroit Diesel Corporation (DDC) DFS93K222, Deutz DQC III-10 LA, IVECO, JASO DH-2, MAN M 3275, MAN M 3575, MB 228.31, MTU Typ 2.1

Application: Truck

RAVENOL Super Low Emission Truck SAE 15W-40 is an all-year engine oil for diesel engines with or without turbo charging, for trucks, busses and work machines.

RAVENOL Super Low Emission Truck SAE 15W-40 is a diesel engine oil with high wear protection, which is also suitable for vehicles with exhaust gas recirculation systems.

RAVENOL Super Low Emission Truck SAE 15W-40 is specially designed for extended oil change intervals (under consideration of the manufacturer instruction).

Characteristics

- High pressure absorption capacity
- High oxidation stability
- Outstanding temperature stability
- Very good detergent and dispersing properties
- Excellent aging resistance
- High wear protection
- Excellent viscosity-temperature behavior
- Neutrality to seals
- High safety reserves even with boundary lubrication conditions
- Best suitability for difficult operating conditions

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rotbraun	VISUELL
Sulphated Ash	%wt.	1	DIN 51575
tbn	mg KOH/g	11	ASTM D2896
Viscosity at 100 °C	mm ² /s	15,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	116,1	DIN 51562-1
Viscosity Index VI		142	DIN ISO 2909
CCS Viscosity at -20 °C	mPa*s	5.370	ASTM D5293
Density at 20 °C	kg/m ³	866,0	EN ISO 12185
Flashpoint	°C	240	DIN EN ISO 2592
Low Temp. Pumping viscosity (MRV) at -40 °C	mPa*s	18.400	ASTM D4684
Noack Volatility	% M/M	7,8	ASTM D5800
Pourpoint	°C	-39	DIN ISO 3016