



RAVENOL Standard Truck SAE 10W



20L | 1123610-020

20L | 1123610-B20

60L | 1123610-060

208L | 1123610-208

1000L | 1123610-700

Kategorie: Truck engine oil

Artikelnummer: 1123610

Viscosity: 10W

Specifications: API CF, API SF

Oil type: Mineral

Recommendations: Allison C4, Caterpillar TO-2, MAN 270, MB 227.0, MIL -L-2104 E, MTU Typ 1, Voith DIWA, Voith Retarder A, ZF TE-ML 02C, ZF TE-ML 03B, ZF TE-ML 04B, ZF TE-ML 06A, ZF TE-ML 07D

Application: Truck

RAVENOL Standard Truck SAE 10W is mineral mono grade motor oil for trucks. All-season oil for all truck diesel engine types. High protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

Application instructions

RAVENOL Standard Truck SAE 10 is mono grade motor oil for use in truck diesel engines. Also suitable for stationary plants.

Characteristics

- Good shear stability
- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
tbn	mg KOH/g	21,0	ASTM D2896
Viscosity at 100 °C	mm ² /s	6,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	36,9	DIN 51562-1
Viscosity Index VI		123	DIN ISO 2909
Density at 20 °C	kg/m ³	862,0	EN ISO 12185
Flashpoint	°C	232	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016