



RAVENOL Standard Truck SAE 40



20L | 1123625-020
208L | 1123625-208
1000L | 1123625-700

Kategorie: Truck engine oil

Artikelnummer: 1123625

Viscosity: 40

Specifications: API CF, API SF

Oil type: Mineral

Recommendations: Allison C4, Caterpillar TO-2, MAN 270, MB 227.0, MIL -L-2104 E, MTU Typ 1 (DDC BR 2000 und 4000), Voith DIWA, Voith Retarder A, ZF TE-ML 02C, ZF TE-ML 03B, ZF TE-ML 04B, ZF TE-ML 06A

Application: Truck

RAVENOL Standard Truck SAE 40 is mineral mono grade motor oil for trucks. All-season oil for all truck diesel engine types. High protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

Application instructions

RAVENOL Standard Truck SAE 40 is mono grade motor oil for use in truck diesel engines. Also suitable for stationary plants.

Characteristics

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts
- Reduced emissions

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
tbn	mg KOH/g	13,0	ASTM D2896
Viscosity at 100 °C	mm ² /s	15,7	DIN 51562-1
Viscosity at 40 °C	mm ² /s	165,8	DIN 51562-1
Viscosity Index VI		97	DIN ISO 2909
Density at 20 °C	kg/m ³	896,0	EN ISO 12185
Flashpoint	°C	254	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016