



# RAVENOL Super Truck SAE 20W-20



5L | 1123715-005  
20L | 1123715-020  
20L | 1123715-B20  
60L | 1123715-060  
208L | 1123715-208

**Kategorie:** Truck engine oil

**Artikelnummer:** 1123715

**Viscosity:** 20W-20

**Specifications:** ACEA B4, ACEA E2, API CF-4

**Oil type:** Mineral

**Recommendations:** MB 228.0

**Application:** Truck

**RAVENOL Super Truck SAE 20W-20** is high alloyed HD engine oil with synthetic additives. It is suitable for diesel engines of trucks even with turbo charging. The high additive content guarantees an excellent effect regarding detergent, dispersant and anti corrosion characteristics.

**RAVENOL Super Truck SAE 20W-20** is a top-quality product with high safety reserves.

## Application instructions

**RAVENOL Super Truck SAE 20W-20** is multi grade motor oil for use in truck diesel engines with or without turbo charger.

## Characteristics

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts
- Reduced emissions

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	8,7	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	60,6	DIN 51562-1
Viscosity Index VI		118	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	870,0	EN ISO 12185
Flashpoint	°C	240	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016