



RAVENOL Super Truck SAE 40

Kategorie: Truck engine oil

Artikelnummer: 1123725

Viscosity: 40

Specifications: ACEA B4, ACEA E2, API CF-4, API SG

Oil type: Mineral

Recommendations: Allison C4, Caterpillar TO-2, Deutz DQC I-02, MAN 270, MB 228.0, MB 235.12, MIL -L-2104 D, MTU Typ 1, ZF TE-ML 02H, ZF TE-ML 04A, ZF TE-ML 04B

Application: Truck



RAVENOL Super Truck SAE 40 is high alloyed HD engine oil with synthetic additives. It is suitable for diesel engines of trucks even with turbo charging. The high additive content guarantees an excellent effect regarding detergent, dispersant and anticorrosion characteristics.

RAVENOL Super Truck SAE 40 is a top-quality product with high safety reserves.

1L | 1123725-001

5L | 1123725-005

10L | 1123725-010

20L | 1123725-020

20L | 1123725-B20

60L | 1123725-060

208L | 1123725-208

1000L | 1123725-700

Application instructions

RAVENOL Super Truck SAE 40 is mono grade motor oil for use in truck diesel engines with or without turbo charger.

Please follow engine manufacturer's recommendations.

Characteristics

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- Good cold start characteristics
- Best corrosion protection
- High safety reserves even with boundary lubrication conditions
- Suitable for catalysts

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		braun	VISUELL
Viscosity at 100 °C	mm ² /s	14,3	DIN 51562-1
Viscosity at 40 °C	mm ² /s	131,5	DIN 51562-1
Viscosity Index VI		108	DIN ISO 2909
Density at 20 °C	kg/m ³	883,0	EN ISO 12185
Flashpoint	°C	246	DIN EN ISO 2592
Pourpoint	°C	-21	DIN ISO 3016