



# RAVENOL TEG 10W-40

**Kategorie:** Other engine oil

**Artikelnummer:** 1132100

**Viscosity:** 10W-40

**Specifications:** ACEA A3/B3, API CF, API SL

**Oil type:** Semi-synthetic

**Application:** Industry



**RAVENOL TEG 10W-40** is high performance semi-synthetic multi-grade engine oil, based on hydrocrack base oils and PAO, suitable for the lubrication of natural gas engines. It has excellent lubricating film adhesion, very good shear stability and an excellent cleaning power and high resistance to aging.

## Application instructions

**RAVENOL TEG 10W-40** is suitable to apply as a multi-grade engine oil for natural gas engines.

## Characteristics

- High wear protection
- Fuel savings through low-friction properties
- Excellent detergent and dispersant properties
- Avoids the formation of accumulations of mud (black sludge)
- Long life due to high oxidation stability
- Excellent cold start performance
- Very good viscosity-temperature behavior
- Low evaporation loss

1L | 1132100-001

4L | 1132100-004

5L | 1132100-005

10L | 1132100-010

20L | 1132100-020

20L | 1132100-B20

60L | 1132100-060

60L | 1132100-D60

208L | 1132100-208

208L | 1132100-D28

1000L | 1132100-700

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	1,3	DIN 51575
tbn	mg KOH/g	10,9	ASTM D2896
Viscosity at 100 °C	mm <sup>2</sup> /s	14,6	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	97,8	DIN 51562-1
Viscosity Index VI		154	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	4900	ASTM D5293
Density at 20 °C	kg/m <sup>3</sup>	857,4	EN ISO 12185
Flashpoint	°C	234	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	4,03	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -30 °C	mPa*s	22000	ASTM D4684
Noack Volatility	% M/M	9,5	ASTM D5800
Pourpoint	°C	-36	DIN ISO 3016