



# RAVENOL MGS SAE 15W-40

**Kategorie:** Other engine oil

**Artikelnummer:** 1133100

**Viscosity:** 15W-40

**Specifications:** ACEA A3/B4, ACEA E2, API CF-4, API SJ

**Oil type:** Mineral

**Approvals:** TEDOM Group 1P (61-0-0281.2)

**Recommendations:** MB 226.9

**Application:** Industry



**RAVENOL MGS SAE 15W-40** is high performance multi-grade engine oil suitable for the lubrication of natural gas engines. It has excellent lubricating film adhesion, very good shear stability and an excellent cleaning power and high resistance to aging.

## Application instructions

**RAVENOL MGS SAE 15W-40** is suitable to apply as a multi-grade engine oil for natural gas engines.

## Characteristics

- A very good shear stability
- Very good cold start behaviour
- A high oxidation stability
- Avoids the formation of accumulations of mud (black sludge)
- An excellent viscosity temperature behaviour
- No problems with the use in catalyst vehicles
- Convincing detergent and dispersant attributes
- High security reserves even under limited lubrication conditions

1L | 1133100-001

4L | 1133100-004

5L | 1133100-005

10L | 1133100-010

20L | 1133100-020

20L | 1133100-B20

60L | 1133100-060

208L | 1133100-208

1000L | 1133100-700

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	1,1	DIN 51575
tn	mg KOH/g	8,1	ASTM D2896
Viscosity at 100 °C	mm <sup>2</sup> /s	14,4	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	107,2	DIN 51562-1
Viscosity Index VI		137	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	873,0	EN ISO 12185
Flashpoint	°C	242	DIN EN ISO 2592
Pourpoint	°C	-30	DIN ISO 3016