



# RAVENOL SCOOTER 2-Takt Fullsynth.



1L | 1151150-001  
4L | 1151150-004  
10L | 1151150-010  
20L | 1151150-020  
20L | 1151150-B20  
60L | 1151150-060  
1000L | 1151150-700

**Kategorie:** 2 stroke engine oil

**Artikelnummer:** 1151150

**Specifications:** API TC, ISO L-EGD

**Oil type:** Full synthetic

**Approvals:** JASO FD (M049RAV153)

**Recommendations:** Aprilia, Honda, Kymco, Peugeot, Piaggio, Suzuki, Vespa, Yamaha

**Application:** Motorcycle

**RAVENOL SCOOTER 2-Takt Fullsynth.** is high quality full synthetic two-stroke engine oil.

**RAVENOL SCOOTER 2-Takt Fullsynth.** with special esters and Polyisobutylene (PIB) and effectively low ash additives for optimum protection against wear and prevent corrosion, deposits and auto-ignitions, even with heavy loads.

**RAVENOL SCOOTER 2-Takt Fullsynth.** is optimized for air- and watercooled two stroke engines in Scooters.

## Application instructions

**RAVENOL SCOOTER 2-Takt Fullsynth.** can generally be mixed with regular petrol 1:100.

**RAVENOL SCOOTER 2-Takt Fullsynth.** is best choice for air- and watercooled two stroke engines in Scooters.

**RAVENOL SCOOTER 2-Takt Fullsynth.** is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

**RAVENOL SCOOTER 2-Takt Fullsynth.** is also suitable for the lubrication of two stroke scooters with water cooling. Suitable for separate lubrication systems and self-mixing systems.

## Characteristics

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from
- combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion
- Very low Pourpoint, also to use at very low temperature

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	10,6	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	67,9	DIN 51562-1
Viscosity Index VI		144	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	865,0	EN ISO 12185
Flashpoint	°C	128	DIN EN ISO 2592
Pourpoint	°C	-39	DIN ISO 3016