



# RAVENOL SCOOTER 4-Takt Fullsynth.



1L | 1151155-001

**Kategorie:** 4 stroke engine oil

**Artikelnummer:** 1151155

**Specifications:** API SN Plus, API SP, SAE 5W-40

**Oil type:** Full synthetic

**Recommendations:** Aprilia, Arctic Cat, Argo, Bombardier, Dinli, Honda, Kawasaki, Peugeot, Piaggio, Polaris, Suzuki, Yamaha

**Application:** Motorcycle

**RAVENOL SCOOTER 4-Takt Fullsynth.** is a full synthetic high quality green colored engine oil for 4-stroke small engines. A specially designed additive package and a formulation with special ingredients for a high viscosity index ensure for a clean engine and clean inlet and exhaust systems and thus proper lubrication and wear protection.

**RAVENOL SCOOTER 4-Takt Fullsynth.** due to its special additives and the selection of base oils and its viscosity an energy-saving operation of engines. Due to its special active ingredients ensures

**RAVENOL SCOOTER 4-Takt Fullsynth.** for a cleaner engine and clean inlet and exhaust systems.

**RAVENOL SCOOTER 4-Takt Fullsynth.** is the product for optimal life of the machine.

**RAVENOL SCOOTER 4-Takt Fullsynth.** ensures excellent cold start performance for optimum lubrication safety in the cold run phase.

## Application instructions

**RAVENOL SCOOTER 4-Takt Fullsynth.** is for use in 4 -Stroke engines.

## Characteristics

- High wear protection
- Fuel savings through smooth running properties
- Excellent detergent and dispersant properties
- Prevention of black sludge formation
- Long life due to high oxidation stability
- Excellent cold start behavior
- Very good viscosity-temperature behavior
- Low evaporation tendency

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		grün	VISUELL
Sulphated Ash	%wt.	1,19	DIN 51575
tbn	mg KOH/g	11,8	ASTM D2896
Viscosity at 100 °C	mm <sup>2</sup> /s	13,3	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	78,2	DIN 51562-1
Viscosity Index VI		173	DIN ISO 2909
CCS Viscosity at -30 °C	mPa*s	5480	ASTM D5293
Density at 20 °C	kg/m <sup>3</sup>	847,0	EN ISO 12185
Flashpoint	°C	240	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	3,91	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	25.000	ASTM D4684
Noack Volatility	% M/M	7,4	ASTM D5800
Pourpoint	°C	-39	DIN ISO 3016