



# RAVENOL WATERCRAFT Fullsynth. 2-Takt



1L | 1151210-001  
4L | 1151210-004  
10L | 1151210-010  
20L | 1151210-020  
20L | 1151210-B20  
60L | 1151210-060  
208L | 1151210-208  
1000L | 1151210-700

**Kategorie:** 2 stroke engine oil

**Artikelnummer:** 1151210

**Specifications:** API TD, ISO L-EGD, JASO FD

**Oil type:** Full synthetic

**Approvals:** NMMA TC-W3, RL-29019G

**Application:** Marine

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** is high quality blue coloured full synthetic two-stroke engine oil.

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** with special esters and Polyisobutylene (PIB) and with effectively two stroke additives.

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** is especially developed for two stroke engines in water vehicles.

## Application instructions

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** can generally be mixed with regular petrol 1:100.

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** is also suitable for the lubrication of two stroke scooters with water cooling.

## Characteristics

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion
- Very low Pourpoint, also to use at very low temperature

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		blau	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	10,8	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	70,7	DIN 51562-1
Viscosity Index VI		128	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	865,0	EN ISO 12185
Flashpoint	°C	143	DIN EN ISO 2592
Pourpoint	°C	-42	DIN ISO 3016