



RAVENOL SNOWMOBILES 4-Takt Fullsynth.

Kategorie: 4 stroke engine oil

Artikelnummer: 1151311

Specifications: API SN

Oil type: Full synthetic

Recommendations: Arctic Cat, Bombardier, Kawasaki, Polaris, Ski-Doo, Suzuki, Yamaha



RAVENOL SNOWMOBILES 4-Takt Fullsynth. is a full synthetic high quality green coloured engine oil based on PAO (Polyalphaolefin).

Due to its special additives and a special formulation **RAVENOL SNOWMOBILES 4-Takt Fullsynth.** achieves an extremely high viscosity stability. The excellent cold start behavior ensures optimum lubrication safety during the cold running phase.

By significantly reducing fuel consumption, **RAVENOL SNOWMOBILES 4-Takt Fullsynth.** helps to protect the environment by reducing emissions.

1L | 1151311-001

4L | 1151311-004

10L | 1151311-010

20L | 1151311-020

20L | 1151311-B20

60L | 1151311-060

208L | 1151311-208

1000L | 1151311-700

Application instructions

RAVENOL SNOWMOBILES 4-Takt Fullsynth. is a fuel-efficient engine oil specifically developed for use in 4 -Stroke Snowmobile engines.

Characteristics

- Quick lubrication of the engine even at temperatures below -30 °C
- Low evaporation tendency, therefore a lower oil consumption
- Safety against accumulation of sludge, coking and corrosion even under unfavourable operating conditions.
- No oil limited deposits in combustion chambers, at the piston ring and valves
- Unchanged viscosity during the whole oil change interval, high viscosity index
- Neutral against sealing materials

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		grün	VISUELL
Sulphated Ash	%wt.	1,3	DIN 51575
tbn	mg KOH/g	12,5	ASTM D2896
Viscosity at 100 °C	mm ² /s	12,0	DIN 51562-1
Viscosity at 40 °C	mm ² /s	60,9	DIN 51562-1
Viscosity Index VI		198	DIN ISO 2909
CCS Viscosity at -35 °C	mPa*s	5610	ASTM D5293
Density at 20 °C	kg/m ³	843,0	EN ISO 12185
Flashpoint	°C	236	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	3,57	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -40 °C	mPa*s	16.300	ASTM D4684
Noack Volatility	% M/M	9,2	ASTM D5800
Pourpoint	°C	-51	DIN ISO 3016