



RAVENOL SCOOTER 4-T 10W-30

Kategorie: 4 stroke engine oil

Artikelnummer: 1152156

Viscosity: 10W-30

Specifications: JASO MB

Oil type: Synthetic



RAVENOL SCOOTER 4-T SAE 10W-30 is a synthetic 4-stroke engine oil with selected additives, which is specially designed for demanding use in scooters and motorcycles.

RAVENOL SCOOTER 4-T SAE 10W-30 has an extremely high oxidation stability and ensures optimum lubrication and operational reliability even under the highest loads.

RAVENOL SCOOTER 4-T SAE 10W-30 has been specially developed (under JASO MB) for use with dry clutches. The oil protects the engine extensively against deposits and thus ensures a long service life. The oil also has a strong wear-reducing effect during cold starts thanks to friction factor-optimizing additives.

1L | 1152156-001

4L | 1152156-004

10L | 1152156-010

20L | 1152156-020

20L | 1152156-B20

60L | 1152156-060

60L | 1152156-D60

208L | 1152156-208

208L | 1152156-D28

Application instructions

RAVENOL SCOOTER 4-T SAE 10W-30 can be used in all 4-stroke scooters, motorcycles and other small motorized vehicles. It is suitable for both air-cooled and water-cooled engines. The operating instructions of the engine manufacturer must be followed.

Characteristics

- High wear protection and shear stability
- Fuel savings due to smooth running properties
- Friction-optimizing additives
- Prevention of black sludge build-up
- Low evaporation tendency
- Excellent cold start behavior
- High functional reserves under extreme lubrication conditions

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		grün-fluoreszierend	VISUELL
Sulphated Ash	%wt.	0,67	DIN 51575
tbn	mg KOH/g	7,1	ASTM D2896
Viscosity at 100 °C	mm ² /s	11,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	75	DIN 51562-1
Viscosity Index VI		149	DIN ISO 2909
Density at 15 °C	kg/m ³	852	EN ISO 12185
CCS Viscosity at -25 °C	mPa*s	5310	ASTM D5293
Flashpoint	°C	264	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	3,57	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -30 °C	mPa*s	14700	ASTM D4684
Noack Volatility	% M/M	3,3	ASTM D5800
Pourpoint	°C	-36	DIN ISO 3016