



# RAVENOL ATV-UTV 4T SAE 5W-40

**Kategorie:** 4 stroke engine oil

**Artikelnummer:** 1152161

**Specifications:** API SN, JASO MA2

**Oil type:** Synthetic

**Recommendations:** Bombardier, CAN-AM, CFMOTO, Honda, Kawasaki, Polaris, Suzuki, Yamaha



**1L | 1152161-001**

**4L | 1152161-004**

**10L | 1152161-010**

**20L | 1152161-020**

**20L | 1152161-B20**

**60L | 1152161-060**

**60L | 1152161-D60**

**208L | 1152161-208**

**208L | 1152161-D28**

**1000L | 1152161-700**

**RAVENOL ATV-UTV 4T SAE 5W-40** is especially developed for demanding use in quads and ATVs (off-road vehicles). It is used for maximum performance and optimum protection in 4-stroke quad engines. Special additives reliably protect the transmission against wear and ease the cranking process with the gear engaged as well as the shifting process itself.

**RAVENOL ATV-UTV 4T SAE 5W-40** enables a low-wear cold start even at very low outside temperatures thanks to its high viscosity. Wear is also minimized in lower gears and with high engine loads.

**RAVENOL ATV-UTV 4T SAE 5W-40** is blended with special additives which reliably protect the gearbox against wear even under high loads and counteract any combustion chamber deposits in the engine.

## Application instructions

**RAVENOL ATV-UTV 4T SAE 5W-40** is used in 4-stroke quad engines from leading manufacturers. It can also be used in vehicles with wet clutches and catalytic converters. It is suitable as an all-year-round oil for quads, but also for other ATV and Enduro vehicles.

**RAVENOL ATV-UTV 4T SAE 5W-40** is designed for all air- and water-cooled 4-stroke engines in the ATV and Enduro range, in accordance to the vehicle manufacturer's operating instructions.

Besides many other vehicles suitable for:

Can-Am (BRP): Maverick (incl. R), Commander, Defender, DS, Renegade, Traxter, Outlander, etc.

Yamaha: Wolverine, Kodiak, Grizzly, Viking, etc.

Honda: FourTrax, Talon, Pioneer, etc.

Kawasaki: Brute Force, Mule, Teryx, KFX, etc.

Polaris: Ranger (gasoline), RZR, Sportsman, Pro XD, Predator, Crew, General, etc.

Suzuki: KingQuad, Quadsport, LTZ, etc.

CFMoto: CFORCE, UFORCE, ZFORCE, etc.

The manufacturer's instructions must be followed!

## Characteristics

- low-wear cold start even at extremely low outside temperatures
- stable lubrication and good shear stability
- compatible with wet clutches and catalytic converters
- can be used all year round
- high corrosion- and wear protection
- low evaporation tendency, therefore low oil consumption
- tested and proven additives
- high safety reserves during peak loads

## Technical Product Data

| CHARACTERISTICS         | PROPERTY | DATA      | AUDIT           |
|-------------------------|----------|-----------|-----------------|
| Colour                  |          | gelbbraun | VISUELL         |
| Sulphated Ash           | %wt.     | 0,87      | DIN 51575       |
| tbn                     | mg KOH/g | 7,2       | ASTM D2896      |
| Viscosity at 100 °C     | mm²/s    | 13,68     | DIN 51562-1     |
| Viscosity at 40 °C      | mm²/s    | 82,97     | DIN 51562-1     |
| Viscosity Index VI      |          | 169       | DIN ISO 2909    |
| CCS Viscosity at -30 °C | mPa*s    | 5937      | ASTM D5293      |
| Density at 20 °C        | kg/m³    | 847       | EN ISO 12185    |
| Flashpoint              | °C       | 244       | DIN EN ISO 2592 |
| Noack Volatility        | %m       | 5,8       | ASTM D5800      |
| Pourpoint               | °C       | -39       | DIN ISO 3016    |