



1L | 1152200-001
4L | 1152200-004
5L | 1152200-005
10L | 1152200-010
20L | 1152200-020
20L | 1152200-B20
60L | 1152200-060
208L | 1152200-208
1000L | 1152200-700

RAVENOL Outboardoil 2T Teilsynth.

Kategorie: 2 stroke engine oil

Artikelnummer: 1152200

Specifications: API TC

Oil type: Semi-synthetic

Approvals: NMMA TC-W3, RL-29018F

Recommendations: Evinrude, Johnson, Mercury, Selva, Suzuki, Tohatsu, Yamaha

Application: Marine

RAVENOL Outboardoil 2T Teilsynth. is high quality 2-stroke engine oil with special esters and Polyisobutylene (PIB) and an ash less additive package for optimum lubricity and excellent corrosion protection.

RAVENOL Outboardoil 2T Teilsynth. is especially designed for use in fresh water-cooled outboard engines with separate (Auto lube systems) or mixed lubrication.

RAVENOL Outboardoil 2T Teilsynth. meets the requirements of the National Marine Manufacturers Association NMMA TC-W3 (CE 50S Yamaha, Mercury).

Application instructions

RAVENOL Outboardoil 2T Teilsynth. is recommended for "TC-W3" Fluids in all outboard engines according to the prescribed mixing ratio from the engine manufacturer. It can also be used for engines operating in seawater. Typical mixing ratio: 1: 75.

Follow the manufacturers recommendations!

Characteristics

- Contains additives, designed on the characteristics of outboard engine
- An excellent corrosion protection in all oil-wetted engine parts
- Immediate, homogeneous mixture with the used fuel (including lead-free)
- An effective pressure and temperature resistant oil film
- An excellent anti-wear performance, high wear protection
- An excellent oxidation stability
- Low coking

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		blau	VISUELL
Viscosity at 100 °C	mm ² /s	9,5	DIN 51562-1
Viscosity at 40 °C	mm ² /s	69,0	DIN 51562-1
Viscosity Index VI		116	DIN ISO 2909
Density at 20 °C	kg/m ³	865,0	EN ISO 12185
Flashpoint	°C	168	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016