



# RAVENOL Selfmix 2T

**Kategorie:** 2 stroke engine oil

**Artikelnummer:** 1153100

**Specifications:** API TC, ISO L-EGB, NMMA TC-W

**Oil type:** Mineral

**Approvals:** JASO FB (M049RAV155)

**Recommendations:** Dolmar, Hitachi, Husqvarna, Jonsered, Makita, Maruyama, McCulloch, Oleo-Mac, Oregon, Partner, Poulan, Ryobi, Stihl

**Application:** Hobby and garden, Motorcycle, Marine



**RAVENOL Selfmix 2T** is a premixed mineral lubricant which meets the exacting demands of two-stroke engines. It effectively prevents the accumulation of carbon deposits in the piston, the combustion chambers and the exhaust ports, and is formulated to avoid contamination of spark plugs and corrosion damage to drive mechanism components.

## Application instructions

**RAVENOL Selfmix 2T** is specially designed for universal use in motorcycles which have separate lubrication and self-mixing systems. When used in separate lubrication systems this product will ensure optimal lubrication and minimizes smoke to help protect the environment. It is suitable for air-cooled as well as water-cooled two-stroke gasoline engines in motorcycles, mopeds and scooters, as well as for other equipment such as lawnmowers etc.

## Characteristics

- Excellent corrosion protection
- Excellent oxidation stability
- Very high wear protection
- Environmentally friendly with low smoke formulation
- Low coking capabilities
- Formulated for universal use

- 0.1L | 1153100-100
- 1L | 1153100-001
- 1L | 1153100-D01
- 4L | 1153100-004
- 10L | 1153100-010
- 20L | 1153100-020
- 20L | 1153100-B20
- 60L | 1153100-060
- 208L | 1153100-208
- 1000L | 1153100-700

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	9,0	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	66,4	DIN 51562-1
Viscosity Index VI		110	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	872,0	EN ISO 12185
Flashpoint	°C	178	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016