



# RAVENOL 2-Taktoel NOT SELFMIX

**Kategorie:** 2 stroke engine oil

**Artikelnummer:** 1153101

**Specifications:** API SA

**Oil type:** Mineral

**Application:** Hobby and garden, Motorcycle, Marine



**RAVENOL 2-Takt-Öl NOT SELFMIX** is mineral high quality two-stroke oil for conventional 2-stroke engines without self-mixing. This unblended oil is produced from carefully selected, pure mineral raffinates. It is resistant to oxidation, non-foaming and has excellent viscosity-temperature characteristics. Due to the low pourpoint, this oil can be used in low as well as high temperatures and ensures an impeccable lubrication.

## Application instructions

**RAVENOL 2-Takt-Öl NOT SELFMIX** is applicable for all conventional two-stroke engines, for which self-mixing is not specified.

## Characteristics

- Excellent viscosity-temperature characteristics
- Good shear stability
- Outstanding oxidation stability
- Good demulsification characteristics

## Technical Product Data

1L | 1153101-001

4L | 1153101-004

10L | 1153101-010

20L | 1153101-020

20L | 1153101-B20

60L | 1153101-060

208L | 1153101-208

1000L | 1153101-700

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	15,7	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	165,8	DIN 51562-1
Viscosity Index VI		97	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	896,0	EN ISO 12185
Flashpoint	°C	254	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016