



RAVENOL Outboardoel 2T Mineral



1L | 1153200-001

1L | 1153200-D01

4L | 1153200-004

5L | 1153200-005

10L | 1153200-010

20L | 1153200-020

20L | 1153200-B20

60L | 1153200-060

208L | 1153200-208

1000L | 1153200-700

Kategorie: 2 stroke engine oil

Artikelnummer: 1153200

Specifications: API TC

Oil type: Mineral

Approvals: NMMA TC-W3, RL-90000G

Recommendations: Evinrude, Johnson, Mercury, Selva, Suzuki, Tohatsu, Yamaha

Application: Marine

RAVENOL Outboardoel 2T Mineral is high quality 2-stroke engine oil based on mineral base oils with an ashless additive package for optimum lubricity and excellent corrosion protection.

RAVENOL Outboardoel 2T Mineral is specifically designed for use in fresh water-cooled outboard engines with separate (Auto lube systems) or mixed lubrication.

RAVENOL Outboardoel 2T Mineral meets the requirements of the National Marine Manufacturers Association NMMA TC-W3.

Application instructions

RAVENOL Outboardoel 2T Mineral is recommended for "TC-W3" Fluids in all outboard engines according to the prescribed mixing ratio from the engine manufacturer. It can also be used for engines operating in seawater.

RAVENOL Outboardoel 2T Mineral is recommended for use in outboard engines of Yamaha, Suzuki, Tohatsu, Johnson, Evinrude, Mercury und Selva.

Typical mixing ratio: 1:50.

Follow the manufacturer's recommendations!

Characteristics

- An excellent corrosion protection in all oil-wetted engine parts
- An excellent oxidation stability
- High wear protection
- Immediate, homogeneous mixture with the used fuel (including lead-free)
- An effective pressure and temperature resistant oil film
- Environmentally friendly with low smoke
- A clean burning with no deposits

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		blau	VISUELL
Sulphated Ash	%wt.		DIN 51575
Viscosity at 100 °C	mm ² /s	66,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	9,0	DIN 51562-1
Viscosity Index VI		110	DIN ISO 2909
Density at 20 °C	kg/m ³	872	EN ISO 12185
Flashpoint	°C	178	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016