



# RAVENOL MARINEOIL SHPD SAE 25W40 synthetic



1L | 1162105-001

4L | 1162105-004

10L | 1162105-010

20L | 1162105-020

20L | 1162105-B20

60L | 1162105-060

208L | 1162105-208

1000L | 1162105-700

**Kategorie:** Marine engine oil

**Artikelnummer:** 1162105

**Viscosity:** 25W-40

**Specifications:** ACEA B4, ACEA E7, API CF, API CI-4

**Oil type:** Synthetic

**Recommendations:** Caterpillar, Detroit Diesel Corporation (DDC), IVECO, MAN, Mercruiser, MTU, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, VETUS DEUTZ, VOLVO, Yanmar

**Application:** Marine

**RAVENOL MARINEOIL SHPD 25W-40 synthetic** is an engine oil for the use in marine diesel engines.

**RAVENOL MARINEOIL SHPD 25W-40 synthetic** is produced with unconventional and HC basic oils, synthetic components and modern additives.

**RAVENOL MARINEOIL SHPD 25W-40 synthetic** guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

## Characteristics

- Excellent detergent and dispersant characteristics
- Low evaporation
- High aging stability
- Protection of reflecting surface formation
- Very good cold start characteristics
- Reduces oil and fuel consumption

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		blau	VISUELL
Sulphated Ash	%wt.	1,3	DIN 51575
tn	mg KOH/g	11,0	ASTM D2896
Viscosity at 100 °C	mm <sup>2</sup> /s	13,5	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	91,8	DIN 51562-1
Viscosity Index VI		148	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	6400	ASTM D5293
Density at 20 °C	kg/m <sup>3</sup>	859,0	EN ISO 12185
Flashpoint	°C	212	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016