



RAVENOL MARINEOIL PETROL SAE 25W40 synthetic



Kategorie: Marine engine oil

Artikelnummer: 1162115

Viscosity: 25W-40

Specifications: ACEA A3/B4, API SL

Oil type: Synthetic

Recommendations: Caterpillar, Detroit Diesel Corporation (DDC), IVECO, MAN, Mercruiser, MTU, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, VETUS DEUTZ, VOLVO PENTA, Yanmar

Application: Marine

RAVENOL MARINEOIL PETROL 25W-40 synthetic is an engine oil for the use in marine petrol engines.

RAVENOL MARINEOIL PETROL 25W-40 synthetic is produced with unconventional and HC basic oils, synthetic components and additives.

RAVENOL MARINEOIL PETROL 25W-40 synthetic guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Characteristics

- Excellent detergent and dispersant characteristics
- Low evaporation
- High aging stability
- Protection of reflecting surface formation
- Very good cold start characteristics
- Reduces oil and fuel consumption

1L | 1162115-001

4L | 1162115-004

10L | 1162115-010

20L | 1162115-020

20L | 1162115-B20

60L | 1162115-060

60L | 1162115-D60

208L | 1162115-208

1000L | 1162115-700

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		blau	VISUELL
Sulphated Ash	%wt.	1,3	DIN 51575
tbh	mg KOH/g	11,0	ASTM D2896
Viscosity at 100 °C	mm ² /s	13,8	DIN 51562-1
Viscosity at 40 °C	mm ² /s	92,4	DIN 51562-1
Viscosity Index VI		152	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	6450	ASTM D5293
Density at 20 °C	kg/m ³	866,0	EN ISO 12185
Flashpoint	°C	215	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016