



# RAVENOL MARINEOIL PETROL SAE 10W-40



1L | 1162200-001  
4L | 1162200-004  
10L | 1162200-010  
20L | 1162200-020  
20L | 1162200-B20  
60L | 1162200-060  
60L | 1162200-D60  
208L | 1162200-208  
1000L | 1162200-700

**Kategorie:** Marine engine oil

**Artikelnummer:** 1162200

**Viscosity:** 10W-40

**Specifications:** API SL

**Oil type:** Semi-synthetic

**Recommendations:** Kohler, Mercruiser, VOLVO PENTA AB, Yanmar

**Application:** Marine

**RAVENOL MARINEOIL PETROL 10W-40** is an engine oil for the use in marine gasoline engines.

**RAVENOL MARINEOIL PETROL 10W-40** is produced with unconventional and HC basic oils, synthetic components and modern additives.

**RAVENOL MARINEOIL PETROL 10W-40** guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

## Characteristics

- Excellent detergent and dispersant characteristics
- Low evaporation
- High aging stability
- Protection of reflecting surface formation
- Very good cold start characteristics
- Reduces oil and fuel consumption

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		blau	VISUELL
Sulphated Ash	%wt.	1,3	DIN 51575
tn	mg KOH/g	11,0	ASTM D2896
Viscosity at 100 °C	mm <sup>2</sup> /s	13,6	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	91,8	DIN 51562-1
Viscosity Index VI		150	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	6480	ASTM D5293
Density at 20 °C	kg/m <sup>3</sup>	866,0	EN ISO 12185
Flashpoint	°C	210	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016