



RAVENOL MARINE 830 SAE 30 TBN8

Kategorie: Marine engine oil

Artikelnummer: 1163001

Viscosity: 30

Specifications: API CC, SAE -Klasse 30

Oil type: Mineral

Recommendations: DEF 2101D, MIL -L-2104 A

Application: Marine



RAVENOL MARINE 830 SAE 30 TBN8 is a mineral diesel engine oil for the navy.

RAVENOL MARINE 830 SAE 30 TBN8 is produced with a special additivation for the demands for a navy oil for the use in crosshead diesel engines and engines for the coasting and inland navigation.

Application instructions

RAVENOL MARINE 830 SAE 30 TBN8 is used as a lubrication oil in slowly running crosshead diesel engines and as an engine oil in easy loaded engines of the coasting and inland navigation.

Characteristics

- a very good oxidation resistance
- a stable viscosity index
- a good neutralizing power to neutralize acid connections which occur when burning diesel fuels
- a good cleaning power
- a good corrosion protection
- a good foam prevention
- a low pourpoint
- a good water separation behaviour

1L | 1163001-001

4L | 1163001-004

10L | 1163001-010

20L | 1163001-020

20L | 1163001-B20

60L | 1163001-060

208L | 1163001-208

1000L | 1163001-700

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		braun	VISUELL
Sulphated Ash	%wt.	1,15	DIN 51575
tn	mg KOH/g	8,5	ASTM D2896
Viscosity at 100 °C	mm ² /s	11,45	DIN 51562-1
Viscosity at 40 °C	mm ² /s	102,0	DIN 51562-1
Viscosity Index VI		99	DIN ISO 2909
Density at 20 °C	kg/m ³	883,0	EN ISO 12185
Flashpoint	°C	264	DIN EN ISO 2592
Pourpoint	°C	-21	DIN ISO 3016