



RAVENOL MARINEOIL DIESEL SHPD SAE 20W-50



1L | 1163110-001

4L | 1163110-004

10L | 1163110-010

20L | 1163110-020

20L | 1163110-B20

60L | 1163110-060

208L | 1163110-208

1000L | 1163110-700

Kategorie: Marine engine oil

Artikelnummer: 1163110

Viscosity: 20W-50

Specifications: ACEA B4, ACEA E7, API CI-4

Oil type: Mineral

Recommendations: Mercruiser, STEYR, Yanmar

Application: Marine

RAVENOL MARINEOIL DIESEL SHPD 20W-50 is a SHPD multi-range engine oil for marine diesel engines.

RAVENOL MARINEOIL DIESEL SHPD 20W-50 corresponds to the demands of the SAE class 20W-50. This viscosity classification guarantees a good lubricating film also under complicate operating conditions.

Characteristics

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions
- a good water separation behaviour

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		blau	VISUELL
Sulphated Ash	%wt.	1,2	DIN 51575
tbn	mg KOH/g	11,2	ASTM D2896
Viscosity at 100 °C	mm ² /s	18,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	161,3	DIN 51562-1
Viscosity Index VI		128	DIN ISO 2909
Density at 20 °C	kg/m ³	878,0	EN ISO 12185
Flashpoint	°C	250	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016