



RAVENOL MARINEOIL SHPD 25W-40 mineral



1L | 1163215-001

4L | 1163215-004

10L | 1163215-010

20L | 1163215-020

20L | 1163215-B20

60L | 1163215-060

208L | 1163215-208

1000L | 1163215-700

Kategorie: Marine engine oil

Artikelnummer: 1163215

Viscosity: 25W-40

Specifications: API CF

Oil type: Mineral

Recommendations: Caterpillar, Detroit Diesel Corporation (DDC), IVECO, MAN, Mercruiser, MTU, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, VETUS DEUTZ, VOLVO PENTA, Yanmar

Application: Marine

RAVENOL MARINEOIL SHPD SAE 25W-40 mineral is a modern high additive treated marine engine oil with synthetic additives. It is suitable for inboard marine diesel engines. The high additive content guarantees an excellent effect on the detergent, dispersant and anti corrosion characteristics. It is a top quality product with high safety reserves.

Application instructions

RAVENOL MARINEOIL SHPD SAE 25W-40 mineral is used in boat engines in case the specification SAE25W-40 is requested.

Characteristics

- suitability for catalysis
- excellent detergent and dispersant characteristics
- very good cold start characteristics
- a high oxidation stability
- an excellent viscosity temperature behaviour
- an excellent corrosion protection
- high safety reserves
- reduction of emissions

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		blau	VISUELL
tbn	mg KOH/g	11,1	ASTM D2896
Viscosity at 100 °C	mm ² /s	19,0	DIN 51562-1
Viscosity at 40 °C	mm ² /s	161,4	DIN 51562-1
Viscosity Index VI		133	DIN ISO 2909
CCS Viscosity at -15 °C	mPa*s	6100	ASTM D5293
Density at 20 °C	kg/m ³	876,0	EN ISO 12185
Flashpoint	°C	245	DIN EN ISO 2592
Pourpoint	°C	-30	DIN ISO 3016