



RAVENOL Motobike 4-T Ester SAE 10W-50



1L | 1171103-001
4L | 1171103-004
10L | 1171103-010
20L | 1171103-020
20L | 1171103-B20
60L | 1171103-060
208L | 1171103-208
1000L | 1171103-700

Kategorie: Motorbike engine oil

Artikelnummer: 1171103

Viscosity: 10W-50

Specifications: API SN

Oil type: Synthetic

Approvals: JASO MA2 T903:2016 (M049RAV176)

Recommendations: Aprilia, BMW, Ducati, Honda, Kawasaki, Moto Guzzi, Suzuki, Triumph, Yamaha

Application: Motorcycle

RAVENOL Motobike 4-T Ester SAE 10W-50 is synthetic engine oil which was especially produced for 4 stroke motorbikes. It provides a fuel saving operation of the engines.

With **RAVENOL Motobike 4-T Ester SAE 10W-50** a solid and high loadable engine oil was developed for superior engines of motorbikes with wet couplings and oil lubricated couplings. The excellent cold start behaviour provides an optimum lubrication safety during the cold run phase.

RAVENOL Motobike 4-T Ester SAE 10W-50 fulfils the high tech demands of the latest powerful engine generation.

Application instructions

RAVENOL Motobike 4-T Ester SAE 10W-50 is suitable as a high performance low friction engine oil for all motorbikes in case the SAE 10W-50 is requested.

Characteristics

- a quick lubrication of the engine
- a low evaporation tendency, therefore a lower oil consumption
- safety against sludge accumulation, cokings and corrosion even under unfavourable operating conditions
- guarantee of the function of the hydro tappets at all temperatures
- no oil limited deposits in combustion chambers, at the piston ring and valves
- unchanged viscosity during the whole oil change interval, a high viscosity index
- neutral against sealing materials

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash		0,85	DIN 51575
tbn	mg KOH/g	7,5	ASTM D2896
Viscosity at 100 °C	mm ² /s	17,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	120,4	DIN 51562-1
Viscosity Index VI		162	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	5914	ASTM D5293
Density at 20 °C	kg/m ³	855	EN ISO 12185
Flashpoint	°C	248	DIN EN ISO 2592
Noack Volatility	% M/M	5,2	ASTM D5800
Pourpoint	°C	-39	DIN ISO 3016