



RAVENOL Motobike 4-T Mineral SAE 20W-40



1L | 1173123-001
4L | 1173123-004
10L | 1173123-010
20L | 1173123-020
20L | 1173123-B20
60L | 1173123-060
208L | 1173123-208

Kategorie: Motorbike engine oil

Artikelnummer: 1173123

Viscosity: 20W-40

Specifications: API SN

Oil type: Mineral

Approvals: JASO MA2 T903:2016 (M049RAV170)

Recommendations: Aprilia, BMW, Ducati, Honda, Kawasaki, Moto Guzzi, Suzuki, Triumph, Yamaha

Application: Motorcycle

RAVENOL Motobike 4-T Mineral 20W-40 is an engine oil on mineral oil base with excellent additives which was especially produced for 4 stroke motorbikes. **RAVENOL Motobike 4-T Mineral 20W-40** was developed for superior engines of motorbikes with wet couplings and oil lubricated couplings.

RAVENOL Motobike 4-T Mineral 20W-40 has an excellent lubricating film adhesive capacity and very good shear stability as well as an excellent cleaning power and a high aging resistance.

Application instructions

RAVENOL Motobike 4-T Mineral 20W-40 is suitable as an engine oil for all motorbikes in case the specification SAE 20W-40 JASO MA/MA2 is requested.

Characteristics

- a very good shear stability
- very good cold start characteristics
- a high oxidation stability
- prevention of black sludge accumulation
- an excellent viscosity temperature behaviour
- suitable for catalyts
- convincing detergent and dispersant characteristics
- high safety reserves even under boundary lubrication conditions

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	0,85	DIN 51575
tbn	mg KOH/g	7,7	ASTM D2896
Viscosity at 100 °C	mm ² /s	14,24	DIN 51562-1
Viscosity at 40 °C	mm ² /s	125,45	DIN 51562-1
Viscosity Index VI		113	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	7830	ASTM D5293
Density at 20 °C	kg/m ³	872,4	EN ISO 12185
Flashpoint	°C	272	DIN EN ISO 2592
JASO T904 DFI		2,04	JASO T904
JASO T904 SFI		1,69	JASO T904
JASO T904 STI		1,98	JASO T904
Noack Volatility	% M/M	2,7	ASTM D5800
Pourpoint	°C	-27	DIN ISO 3016