



RAVENOL GHA-F Gearbox Hydraulic Actuator Fluid

Kategorie: Car hydraulic oil

Artikelnummer: 1181201

Oil type: Mineral

Recommendations: Fiat 14621616, Fiat 9.55550-SA1, Fiat F005.F98, Fiat/Alfa Romeo 15081616 CS SPEED für Dualogic, Peugeot/Citroën 9979.A4 für MCP Automated Gearbox, Suzuki 99000M24121-135, Suzuki AMT Actuator Fluid

Application: Passenger car



1L | 1181201-001
20L | 1181201-B20

RAVENOL Gearbox Hydraulic Actuator Fluid GHA-F is a special hydraulic fluid, based on synthetic and mineral oil with non-ash forming additives.

The properties of **RAVENOL Gearbox Hydraulic Actuator Fluid GHA-F** are decisively determined by its special formulation. We guarantee an excellent low temperature stability.

Application instructions

RAVENOL Gearbox Hydraulic Actuator Fluid GHA-F is designed for a range of application from -40°C to $+100^{\circ}\text{C}$.

RAVENOL Gearbox Hydraulic Actuator Fluid GHA-F is used in electrically controlled MCP gearboxes from Peugeot/Citroën and in Dualogic and Selespeed gearboxes from FIAT/Alfa Romeo and therefore, shows ideal performance as a special hydraulic fluid in electrohydraulic and electrically controlled gears and gearshifts.

Characteristics

- Extremely low pour point.
- Improved viscosity and friction value characteristics.
- Very good wear protection.
- An excellent thermal stability.
- Improved EP properties.
- Good foaming characteristics.
- Neutral behaviour towards sealing compounds.
- Reliable protection against corrosion.

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		grün	VISUELL
Viscosity at 100 °C	mm ² /s	6,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	19,7	DIN 51562-1
Viscosity Index VI		333	DIN ISO 2909
Density at 20 °C	kg/m ³	827,0	EN ISO 12185
Flashpoint	°C	164	DIN EN ISO 2592
Pourpoint	°C	-54	DIN ISO 3016