



RAVENOL FORKOIL Medium 10W

Kategorie: Motorbike hydraulic oil

Artikelnummer: 1182104

Viscosity: 10W

Oil type: Mineral

Recommendations: Aprilia, BMW, Ducati, Honda, Kawasaki, Moto Guzzi, Suzuki, Triumph, Yamaha

Application: Motorcycle



1L | 1182104-001

4L | 1182104-004

20L | 1182104-B20

60L | 1182104-060

RAVENOL FORKOIL Medium 10W is a fork oil on mineral oil base which was developed for all forks of off-road motorbikes and motor cross bikes.

RAVENOL FORKOIL Medium 10W is especially characterised by a high and stable viscosity index as well as a solid corrosion protection. Efficient additives offer even under extreme loads an excellent corrosion protection. The behaviour against sealing materials is neutral.

Application instructions

RAVENOL FORKOIL Medium 10W was developed for the use in all chassis components of two-wheeler vehicles and offers good power characteristics. In order to obtain the optimum viscosity for the vehicle and operating condition the mineral fork oils are miscible among each other.

Characteristics

- good damping characteristics at all temperatures
- a high and stable viscosity index
- an excellent protection against corrosion, therefore a longer endurance of the fork components
- as far as possible protection against corrosion of the inside components
- a very good air and water separation behaviour to prevent foam formation
- neutral behaviour against sealings made of plastics
- a very low pour point

Technical Product Data

| CHARACTERISTICS | PROPERTY | DATA | AUDIT |
|---------------------|--------------------|-------|-----------------|
| Colour | | gelb | VISUELL |
| Sulphated Ash | %wt. | 0,06 | DIN 51575 |
| tn | mg KOH/g | 0,4 | ASTM D2896 |
| Viscosity at 100 °C | mm ² /s | 6,6 | DIN 51562-1 |
| Viscosity at 40 °C | mm ² /s | 32,8 | DIN 51562-1 |
| Viscosity Index VI | | 162 | DIN ISO 2909 |
| Density at 20 °C | kg/m ³ | 846,0 | EN ISO 12185 |
| Flashpoint | °C | 228 | DIN EN ISO 2592 |