



1L | 1211100-001  
4L | 1211100-004  
10L | 1211100-010  
20L | 1211100-020  
20L | 1211100-B20  
60L | 1211100-060  
208L | 1211100-208

# RAVENOL ATF+4 Fluid

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1211100

**Oil type:** Synthetic

**Approvals:** Chrysler License-No. 40630041 FCA US LLC

**Recommendations:** Chrysler MS-9602, Fiat 9.55550-AV4, Mopar 68218054GA, Mopar 68218057GA, Mopar 68218058GA

**Application:** Passenger car

**RAVENOL ATF+4® Fluid** is a synthetic, licensed automatic transmission fluid ATF with an unique additive package for Fiat-Chrysler, Jeep and Dodge automatic transmission.

**RAVENOL ATF+4® Fluid** guarantees maximum wear protection in all operating conditions.

**RAVENOL ATF+4® Fluid** is mixable with all ATF+4®, ATF+2® or ATF+3® transmission oil.

## Application instructions

**RAVENOL ATF+4® Fluid** is recommended for refilling and fill up automatic transmission oil for Fiat-Chrysler, Dodge, Plymouth, RAM, Jeep and Eagle vehicles with automatic transmission.

**RAVENOL ATF+4® Fluid** achieves the warranty of FCA US LLC (Fiat Chrysler Automobiles) and is released with License-No. 40630041.

**RAVENOL ATF+4® Fluid** meets the requirements of current and previous standards for Fiat-Chrysler, Dodge, Plymouth, Jeep and Eagle automatic transmission oil.

## Characteristics

- Better protection and better performance than ATF+3®
- Extended transmission life
- Reduces maintenance costs
- Better shift quality through a consistent viscosity profile
- Better cold flow properties
- Smooth switching at low temperatures
- Less transmission wear when operating at low temperatures
- Better oxidation stability and thermal stability than the previous ATF+3®
- Longer oil life period
- Lower oil consumption
- Better fuel economy
- Longer oil change intervals (has been tested extensively with oil change intervals of about 160,000 km)

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	7,5	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	35,1	DIN 51562-1
Viscosity Index VI		192	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	6.500	ASTM D2983
Density at 20 °C	kg/m <sup>3</sup>	845,0	EN ISO 12185
Flashpoint	°C	198	DIN EN ISO 2592
Pourpoint	°C	-63	DIN ISO 3016