



RAVENOL ATF Dexron II E

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211103

Specifications: Ford MERCON®, GM Dexron® II E

Oil type: Synthetic

Approvals: Allison C4-32652009 (ATF II E), MB -Freigabe 236.8, Voith H55.6336.3x Extended Drain (G1363)

Recommendations: Caterpillar TO-2, DTFR 13C150 (MB 236.8), MAN 339 V2, MAN 339 Z2, MB 236.5, ZF TE-ML 04D, ZF TE-ML 09X, ZF TE-ML 14B, ZF TE-ML 16L

Application: Truck, Passenger car



RAVENOL ATF Dexron II E is high performance synthetic automatic transmission oil ATF for use in torque converter transmission and power shift transmission of vehicles with specification GM Dexron II E, Ford Mercon and Allison C-4.

Application instructions

RAVENOL ATF Dexron II E is developed for use in automatic transmission and torque converter transmission and power shift transmission with required specification.

RAVENOL ATF Dexron II E is recommended if ATF Type Dexron II E is to be used according to manufacturer's specification.

Characteristics

- reliable protection against wear, sludge, adhesion and corrosion
- a very shear stable viscosity-temperature behaviour
- can be used both at very low and very high temperatures
- an extremely high thermal load
- no foaming, even under the heaviest loads
- compatibility with sealing materials

1L | 1211103-001

4L | 1211103-004

10L | 1211103-010

20L | 1211103-020

20L | 1211103-B20

60L | 1211103-060

60L | 1211103-D60

208L | 1211103-208

208L | 1211103-D28

1000L | 1211103-700

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
tbn	mg KOH/g	1,7	ASTM D2896
Viscosity at 100 °C	mm ² /s	7,5	DIN 51562-1
Viscosity at 40 °C	mm ² /s	32,0	DIN 51562-1
Viscosity at -40 °C	mPa*s	8.300	ASTM D2983
Viscosity Index VI		191	DIN ISO 2909
Density at 20 °C	kg/m ³	834,0	EN ISO 12185
Flashpoint	°C	226	DIN EN ISO 2592
Pourpoint	°C	-57	DIN ISO 3016