



RAVENOL CVT Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211110

Oil type: Synthetic



Recommendations: BMW CVT EZL 799A, Chery 018CHA/QR018CHA, Chery 025CHA/QR025CHA, Chery 025CHA-4004011AA10, Chery 025CHC/QR025CHC, Chery CVT18, Chery CVT25, Chery CVTF WCF-1, Ford Five Hundred CFT30, Ford EU WSS-M2C-928 A, Ford Focus C-Max CFT23, Ford USA WSS-M2C933-A, Ford XT-7-QCFT Freestyle, HMMF Ultra Fluid 08260-99904, HMMF Ultra Fluid 08260-99907, Honda CVT Fluid 08200-9006, Mazda TFF CVT Fluid TC JWS3320 K020-W0-051W, MB 236.20 (A 001 989 46 03), Mini Cooper CVT, Nissan CVT Fluid NS-1, Nissan KLE50 00002, Nissan KLE50 00004, Opel/GM 1940713, Punch Powertrain VT1F, Punch Powertrain VT2, Punch Powertrain VT3, Subaru CVT Lineartronic II K0425Y0711, Subaru i-CVT Fluid K0415-YA090, Suzuki S-CVT 99000-22801-000, VW TL 52180, Toyota CVT Fluid TC 08886-02105, VW G 052 516 A2, VW/Audi G 052 180 A1, VW/Audi G 052 180 A2, VW/Audi G 052 180 A6

Application: Passenger car

RAVENOL CVT Fluid is a synthetic ATF for the latest generation of CVT transmission.

RAVENOL CVT Fluid guarantees an optimum of power transmission.

RAVENOL CVT Fluid is based on high-quality hydrocrack oils with special additives and inhibition to ensure the proper operation of the automatic transmission.

Application instructions

RAVENOL CVT Fluid was developed for use in CVT transmission (Steel Belt Continuously Variable Transmission).

RAVENOL CVT Fluid ensures a stable viscosity under high mechanical stress in the transmission elements (push belt).

Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very low pour point
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- Neutral behaviour towards sealing materials
- Neutral behaviour by inhibition to non-ferrous metals

1L | 1211110-001

4L | 1211110-004

10L | 1211110-010

20L | 1211110-020

20L | 1211110-B20

60L | 1211110-060

60L | 1211110-D60

208L | 1211110-208

208L | 1211110-D28

1000L | 1211110-700

Technical Product Data

| CHARACTERISTICS | PROPERTY | DATA | AUDIT |
|---------------------|--------------------|-----------|--------------|
| Colour | | gelbbraun | VISUELL |
| Viscosity at 100 °C | mm ² /s | 7,3 | DIN 51562-1 |
| Viscosity at 40 °C | mm ² /s | 35,5 | DIN 51562-1 |
| Viscosity Index VI | | 175 | DIN ISO 2909 |
| Density at 20 °C | kg/m ³ | 841,0 | EN ISO 12185 |
| Pourpoint | °C | -48 | DIN ISO 3016 |