



# RAVENOL ATF J2/S Fluid

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1211115

**Oil type:** Synthetic

**Recommendations:** Mitsubishi 4031610 ATF Fluid J3, Mitsubishi MZ313771 ATF Fluid J2, Nissan 999MP-MTJ00P Matic Fluid J, Nissan 999MP-MTS00P Matic Fluid S, Nissan KE908-99932 Matic Fluid J, Nissan KLE2300002 Matic Fluid J, Nissan KLE24 00002 Matic Fluid S, Renault Matic J6

**Application:** Passenger car



**RAVENOL ATF J2/S Fluid** is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

**RAVENOL ATF J2/S Fluid** is specifically designed for all 5, 6 and 7-speed JATCO automatic transmissions.

**RAVENOL ATF J2/S Fluid** ensures maximum wear protection and smooth shifting in all conditions.

**RAVENOL ATF J2/S Fluid** is red colored.

1L | 1211115-001

4L | 1211115-004

10L | 1211115-010

20L | 1211115-020

20L | 1211115-B20

60L | 1211115-060

60L | 1211115-D60

208L | 1211115-208

208L | 1211115-D28

1000L | 1211115-700

## Application instructions

**RAVENOL ATF J2/S Fluid** is designed specifically for use in JATCO automatic transmissions as follows; JF613E - Renault gearbox AJ0 Laguna, Scenic, Espace, Latitude; Nissan Qashqai transmission AJ0; Mitsubishi Outlander Transmission F6AJA and W6AJA; JR710E and JR711E - Infiniti FX50, EX37, NISSAN FAIR LADY Z, SKYLINE, FUGA.

## Characteristics

- Excellent lubricity even at low temperatures in winter
- High and stable viscosity index
- Very good oxidation stability
- Extensive protection against wear, corrosion and foaming
- High thermal and oxidative stability
- An excellent cooling capability

## Technical Product Data

| CHARACTERISTICS  | PROPERTY          | DATA  | AUDIT        |
|------------------|-------------------|-------|--------------|
| Colour           |                   | rot   | VISUELL      |
| Density at 20 °C | kg/m <sup>3</sup> | 838,0 | EN ISO 12185 |
| Pourpoint        | °C                | -51   | DIN ISO 3016 |