



RAVENOL PSF-Y Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211123

Oil type: Synthetic

Recommendations: Chrysler 04883077, Chrysler 05098158A, Chrysler MS-10838, Chrysler MS-5931, Chrysler MS-9933, DTFR 38B100 (MB 236.3), GM 1050017, GM 89020661, GM 9985010, Honda 08206-9002, Honda 08285-P99-01Z-T1, MB 236.3, MB (A 000 989 88 03), Mopar 05142893AA, Texaco TL 4634, VW G 009 300 A2

Application: Passenger car



RAVENOL PSF-Y Fluid is a synthetic Special Fluid, designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the power steering.

Due to its special formulation the properties of **RAVENOL PSF-Y Fluid** are crucial. We assure an excellent cold stability.

Application instructions

RAVENOL PSF-Y Fluid is specially designed for use in the latest power steering of Volkswagen, Mercedes and Chrysler. Please note: Follow manufacturer's original equipment number!

Characteristics

- Extremely low pour point
- Improved viscosity and coefficient of friction behaviour
- A very good protection against consumption
- Excellent thermal stability
- Improved EP-characteristics
- A good foaming behaviour
- Neutral behaviour towards sealing materials
- Reliable protection against corrosion

1L | 1211123-001

4L | 1211123-004

20L | 1211123-020

20L | 1211123-B20

60L | 1211123-060

60L | 1211123-D60

208L | 1211123-208

208L | 1211123-D28

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	7,2	DIN 51562-1
Viscosity at 40 °C	mm ² /s	34,9	DIN 51562-1
Viscosity Index VI		177	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	12800	ASTM D2983
Density at 20 °C	kg/m ³	849,0	EN ISO 12185
Flashpoint	°C	210	DIN EN ISO 2592
Pourpoint	°C	-51	DIN ISO 3016