



RAVENOL Transfer Fluid DTF-1

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1211128

Oil type: Full synthetic

Recommendations: ATC300, ATC350, ATC400, ATC450, ATC500, ATC700, ATF TF-0753, ATF TF-0870, BMW 83220306816 für Transfer Case xDrive, BMW 83222397244, BMW DTF-1 83222409710, Genesis (USA) 5.0 GDI AWD, Genesis (USA) G90 3.3 T-GDI, KIA (EU) 3.3 T-GDI AWD, KIA (EU) Stinger 2.2 CRDI, Land Rover IYK500010, MB 235.64, MB 239.41 Torque-on-Demand (TOD) Verteilergetriebe, Mopar 68049954AA für BorgWarner 44-40 Verteilgetr., Nissan 999MP-ATFD3MP, Nissan 999MP-TF0870P, Nissan KLD22-00001EU für Transfer Case ATX90A, Porsche 000.043.301.36, Porsche 000.043.305.63, VW G 052 515 A2, VW G 052 533 A2, VW G 052 536 A2, VW G 055 512 A2

Application: Passenger car



RAVENOL Transfer Fluid DTF-1 is a PAO (Poly-alpha-olefin) based, full synthetic Transfer Fluid) with a special additive and inhibition, which ensure the proper functioning of the active transfer case.

RAVENOL Transfer Fluid DTF-1 is a full synthetic gear lubricant for use in electronically controlled active transfer case.

RAVENOL Transfer Fluid DTF-1 ensures optimum power transmission.

1L | 1211128-001
4L | 1211128-004
10L | 1211128-010
20L | 1211128-020
20L | 1211128-B20
60L | 1211128-060

Application instructions

RAVENOL Transfer Fluid DTF-1 was developed for use in active transfer case (Active Transfer Case).

RAVENOL Transfer Fluid DTF-1 provides a stable viscosity even under the highest loads.

RAVENOL Transfer Fluid DTF-1 is tried and tested for aggregates specifying:

Land Rover IYK500010, ATF TF-0753, ATF TF-0870;

MB 239.41 Torque-on-Demand (TOD) Transfer case in Type 167 GLE, Type 463 G-Class, Type 470 X-Class, Type 471 with engine OM642;

Porsche 000.043.301.36 Cayenne 9PA/9PA1 955 / 957 (from 2002 to 2010) Transfer Case PL72 ATC (NV325), 000.043.305.63 Porsche Macan 95B (from 2014) and Cayenne 92A / 958 (Petrol engines from 2010 to 2018) Transfer Case Hang-On PL72 ATC;

VW G052 515 A2 (afterwards: G055 515 A2) for Transfer Case 0AD and 0BV for Touareg, Q7; VW G052 533 A2 for Transfer Case 0C7 for Amarok; VW G052 536 A2 for Transfer Case 0BU for Touareg, Amarok and Audi Q7

Characteristics

- Very good lubricating ability even at very low temperatures in winter

- A high, stable viscosity index
- Very good oxidation stability
- Protection against wear, corrosion and foam formation
- Good balanced coefficient of friction
- Neutral towards sealing materials
- Neutral behavior by inhibition compared with non-ferrous metals

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Density at 20 °C	kg/m ³	831,0	EN ISO 12185
Pourpoint	°C	-63	DIN ISO 3016