



RAVENOL CVTF NS3/J4 Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211132

Oil type: Synthetic

Recommendations: 999MP-NS300P, ATF J4, ATF NS-3, Mitsubishi MZ102658, Mitsubishi MZ320261, Mitsubishi MZ320262, Mitsubishi MZ320288, Nissan KLE53-00002, Nissan KLE53-00004, Suzuki CVT Fluid Green-2 99000-22B24-046, Suzuki CVT Fluid Green-2 990N0-22B24-004

Application: Passenger car



RAVENOL CVTF NS3/J4 Fluid is a synthetic CVTF (Continuously Variable Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the CVT transmission.

RAVENOL CVTF NS3/J4 Fluid is a CVTF of the latest generation. It is especially developed for the CVT transmission of JATCO. It guarantees in any mode for maximum wear protection.

RAVENOL CVTF NS3/J4 Fluid is green colored.

1L | 1211132-001

4L | 1211132-004

10L | 1211132-010

20L | 1211132-020

20L | 1211132-B20

60L | 1211132-060

208L | 1211132-D28

Application instructions

RAVENOL CVTF NS3/J4 Fluid is suitable for use in CVT transmission of following vehicles:

Nissan Qashqai J11 2013-, Nissan Pathfinder R52 2013-, Nissan Altima L33 2013-, Nissan Teana L33 2013-, Nissan Sylphe B17 2012-, Nissan Tiida C12 2014-, Nissan X-Trail T32 2013-, Nissan Elgrand E52 2013-, Nissan Murano Z51 2013-, Nissan Murano Z52 2015-, Mitsubishi Outlander GF7W/8W 2012-, Mitsubishi Delica D5 2012-, Mitsubishi Lancer 2012-, Mitsubishi ASX 2014-, Renault Koleos 2014-, Samsung QM5 2013-, Peugeot 4008 2014-, Citroen C4 Aircross 2014- and others with CVT-transmission JATCO JF016E or JF017E.

Maintenance-filling under normal operating conditions.

Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		grün	VISUELL
Density at 20 °C	kg/m ³	836,0	EN ISO 12185
Pourpoint	°C	-57	DIN ISO 3016