



RAVENOL ATF M 9-G Serie

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211139

Oil type: Synthetic

Recommendations: ATF D971, MB 236.17, MB (A 002 989 06 03), Nissan 999MP-MTP10P, Nissan ATF Matic P

Application: Passenger car



RAVENOL ATF M 9-G Serie is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

RAVENOL ATF M 9-G Serie is an ATF (Automatic Transmission Fluid) developed for all 9-gear automatic transmissions (9G-Tronic) of motor vehicles by Mercedes-Benz. Guarantees maximum wear protection in every operating state.

Application instructions

RAVENOL ATF M 9-G Serie was developed for use in the 9G-Tronic automatic transmission of the Series W9A 700 by Mercedes-Benz and JR913E from Jatco for Nissan Titan 2020 – 2024, Nissan Frontier from 2020- and Nissan Z (RZ34) 2023-). These Transmissions are also known under the name NAG3 (New Automatic Transmission of the 3rd Generation) of the type 725.011.

RAVENOL ATF M 9-G Serie can also be used in aggregates with the specification MB 236.16 (A 001 989 92 03), since these were replaced by the new specification MB 236.17.

RAVENOL ATF M 9-G Serie must not be used in older Mercedes Benz 5 and 7-gear automatic transmission, which require automatic transmission oil according to the MB approval MB 236.10, 236.12, 236.14 or 236.15.

Characteristics

- Very good lubricity even at low temperatures in winter, very low pour point
- High, stable viscosity index
- Very good oxidation stability
- Broadest protection against wear, corrosion and foaming
- An excellent shear stability due to a high thermal and oxidative stability
- An excellent friction characteristic
- An excellent cooling capability

1L | 1211139-001

4L | 1211139-004

10L | 1211139-010

20L | 1211139-020

20L | 1211139-B20

60L | 1211139-060

208L | 1211139-208

1000L | 1211139-700

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Density at 20 °C	kg/m ³	834,0	EN ISO 12185
Pourpoint	°C	-54	DIN ISO 3016