



RAVENOL ATF 9HP Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211149

Oil type: Full synthetic

Recommendations: Acura 08200-9016A, Acura ATF Type 3.0, ATF L 12108, ATF Type 3.1, BMW 83222167720, BMW 83222305397 (83222152426), Fiat 9.55550-AV5, Honda 08200-9170, Jaguar Land Rover LR023288, Jaguar Land Rover LR023289, MB 236.82 (A 000 989 65 05), Mopar 68157995AB, Mopar 68218925AA, VW/Audi G 055 162, VW/Audi G 060 162 A1, VW/Audi G 060 162 A6, VW/Audi G 060 162 A2, ZF S671 090 312, ZF TE-ML 11 9HP48

Application: Passenger car



RAVENOL ATF 9HP Fluid is a full synthetic ATF (Automatic Transmission Fluid), designed on the basis of PAO (Poly-alpha-olefin) with a special additivation and inhibition, which ensure a proper function of the automatic transmission.

RAVENOL ATF 9HP Fluid is an automatic transmission fluid (ATF) of the latest generation for all 9 stroke automatic transmissions of ZF. It guarantees maximum wear protection in any operating condition.

RAVENOL ATF 9HP Fluid is green coloured.

1L | 1211149-001

4L | 1211149-004

10L | 1211149-010

20L | 1211149-020

20L | 1211149-B20

60L | 1211149-060

60L | 1211149-D60

208L | 1211149-208

208L | 1211149-D28

Application instructions

RAVENOL ATF 9HP Fluid is suitable for use in automatic ZF transmission of 9HP-Series, such as 9HP48. Please observe OEM Part Numbers and their regulations!

Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against wear, corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		grün	VISUELL
Viscosity at 100 °C	mm ² /s	5,5	DIN 51562-1
Viscosity at 40 °C	mm ² /s	24,7	DIN 51562-1
Viscosity Index VI		171	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	6940	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m ³	840	EN ISO 12185
Flashpoint	°C	218	DIN EN ISO 2592
Pourpoint	°C	-54	DIN ISO 3016