



RAVENOL ATF MERCON® V

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1212101

Specifications: FORD MERCON® V

Oil type: Synthetic

Approvals: Ford MERCON® V (Lizenznummer M5060502)

Recommendations: Ford 8000045, Ford ATF E-M5, Ford WSS-M2C202-B, Ford WSS-M2C919-E, Ford XT-5-QMC, Ford 1565889, Ford 5014519, Ford XT-5-5QM, Ford XT-5-DMC

Application: Passenger car



RAVENOL ATF MERCON® V is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

RAVENOL ATF MERCON® V guarantees a maximum of corrosion protection during any operating condition.

RAVENOL ATF MERCON® V is a ATF (Automatic Transmission Fluid ATF for automatic transmissions of FORD.

1L | 1212101-001

4L | 1212101-004

10L | 1212101-010

20L | 1212101-020

20L | 1212101-B20

60L | 1212101-060

60L | 1212101-D60

208L | 1212101-208

208L | 1212101-D28

1000L | 1212101-700

Application instructions

RAVENOL ATF MERCON® V was especially developed for the use in automatic transmissions of FORD. It is recommended to flush with **RAVENOL ATF MERCON® V** before filling.

Characteristics

- a very good lubricating ability even at low temperatures in winter
- a high, stable viscosity index
- a very low pour point
- a very good oxidation stability
- as far as possible protection against corrosion and foam formation
- good balanced coefficient of friction
- neutral behaviour against sealing materials
- neutral behaviour because of inhibition against non-ferrous metals

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
Viscosity at 100 °C	mm ² /s	7,2	DIN 51562-1
Viscosity at 40 °C	mm ² /s	34,8	DIN 51562-1
Viscosity Index VI		178	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	15.800	ASTM D2983
Density at 20 °C	kg/m ³	847,0	EN ISO 12185
Flashpoint	°C	210	DIN EN ISO 2592
Pourpoint	°C	-48	DIN ISO 3016