



RAVENOL ATF Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1213101

Oil type: Mineral

Recommendations: Allison C4, Caterpillar TO-2, DTFR 13C120 (MB 236.2), MAN 339 A, MB 236.2, Renk Doromat, Type A Suffix A (TASA)

Application: Oldtimer, Passenger car



RAVENOL ATF Fluid is designed on the basis of mineral refined base oils with a special additive and inhibition, which guarantee a perfect function.

RAVENOL ATF Fluid is a very high quality mineral gear fluid for automatic fluid couplings and torque converters as well as power steering aids.

Application instructions

RAVENOL ATF Fluid should be used according to the instructions of the unit manufacturer in: Automatic transmissions, turbo couplings, servo clutches and other hydrostatic and hydrodynamic systems.

RAVENOL ATF Fluid must not be used if ATF Type DEXRON B or DEXRON D or ATF Type M2C-33 E / F / G are expressly mentioned as filling instructions.

Characteristics

- Exceptionally good resistance to aging
- A very good viscosity-temperature behaviour
- Effective protection against wear
- Very good oxidation stability and low foaming tendency
- Enhanced protection against corrosion
- An extremely low pour point
- Compatible with all types of sealing materials
- Miscibility and compatibility with all brands of ATF's with Type A Suffix A specification

1L | 1213101-001

4L | 1213101-004

10L | 1213101-010

20L | 1213101-020

20L | 1213101-B20

60L | 1213101-060

208L | 1213101-208

1000L | 1213101-700

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		Rot	VISUELL
Viscosity at 100 °C	mm ² /s	7,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	34,6	DIN 51562-1
Viscosity Index VI		187	DIN ISO 2909
Density at 20 °C	kg/m ³	848,0	EN ISO 12185
Flashpoint	°C	210	DIN EN ISO 2592
Pourpoint	°C	-48	DIN ISO 3016