



RAVENOL ATF Dexron D II

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1213102

Specifications: Allison C3, Allison C4, GM Dexron® II D

Oil type: Mineral

Approvals: Voith H55.6335.xx

Recommendations: Caterpillar TO-2, CVT, DTFR 13C140 (MB 236.7), Ford M2C-138 CJ, Ford M2C-166H, Ford M2C-185A, Ford MERCON®, Ford SQM-9010B, MAN 339 Z1, MB 236.6, MB 236.7, Renk Doromat, ZF TE-ML 03D, ZF TE-ML 04D, ZF TE-ML 05L, ZF TE-ML 11A, ZF TE-ML 14A, ZF TE-ML 17C

Application: Oldtimer, Passenger car, Truck



RAVENOL ATF Dexron D II is a first class transmission fluid for automatic transmissions of all vehicles and working machines on the basis of high refined mineral oils with a corresponding additive treatment.

Application instructions

RAVENOL ATF Dexron D II was developed for the use in automatic transmissions, hydro steering mechanisms, converters and power transmissions and can be used as a universal ATF (Automatic-Transmission-Fluid) for all vehicles and working machines.

Characteristics

- protection against corrosion, sludge and sticking
- an excellent and very shear stable viscosity temperature behaviour
- no problems concerning very low respectively very high temperatures
- an excellent high thermal capacity
- free of foam even under hardest loads
- neutral behaviour against sealing materials
- mixable and compatible with all kinds of ATF

1L | 1213102-001

4L | 1213102-004

10L | 1213102-010

20L | 1213102-020

20L | 1213102-B20

208L | 1213102-208

208L | 1213102-D28

1000L | 1213102-700

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		Rot	VISUELL
Viscosity at 100 °C	mm ² /s	7,3	DIN 51562-1
Viscosity at 40 °C	mm ² /s	34,3	DIN 51562-1
Viscosity Index VI		185	DIN ISO 2909
Density at 20 °C	kg/m ³	848,0	EN ISO 12185
Flashpoint	°C	210	DIN EN ISO 2592
Pourpoint	°C	-51	DIN ISO 3016