



RAVENOL MTF-2 SAE 75W-80

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1221103

Viscosity: 75W-80

Specifications: API GL-4, API MT-1

Oil type: Full synthetic



Recommendations: AC Delco 10-403, Audi G052532, Audi G055532, BMW 23001434404 MTF-LT-1, BMW 23007533513 MTF-LT-2, BMW 83220309031 MTF-LT-1, Fiat 14621616, Fiat 9.55550-MZ2, Fiat F178.B06, Ford 1382914, Ford 1547953, Ford WSS-M2C200-C3, Ford WSS-M2C200-D2, GM 1940711, GM 88861800, GM 88861801, Honda 08261-99964 Genuine MTF Fluid, Honda 08798-9031 MTF-7289, Hyundai 02200-00130 TOD, Jaguar Land Rover STC 9157, Jaguar Land Rover STC 9158, Land Rover TYK500030, MB 235.10 (A 001 989 26 03), Mitsubishi 3005401, Mitsubishi MZ312644, Land Rover, MG und MINI MTF-94 Fluid, Nissan 999MP-MTF20P, Nissan KE91699932R, Peugeot 9730A2, PSA B71 2330, Subaru K0321-F0090, Toyota 08885-00705, Toyota MTF 97309, Toyota MTF ETL8997B, Toyota MTF XT4447 M+, VOLVO 1161681, VOLVO 1161745, VW/Audi G 052 911 A2, VW/Audi G 055 538 A2 für ZF 6S450 Amarok 0C6

Application: Passenger car

RAVENOL MTF-2 SAE 75W-80 is a PAO based full synthetic low-viscosity transmission oil for modern manual transmission.

RAVENOL MTF-2 SAE 75W-80 is designed based on special selected base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

RAVENOL MTF-2 SAE 75W-80 is outstanding for use under severe mechanical and thermal stress on transmission oils, even with extended oil change intervals.

1L | 1221103-001

4L | 1221103-004

10L | 1221103-010

20L | 1221103-020

20L | 1221103-B20

60L | 1221103-060

60L | 1221103-D60

208L | 1221103-208

208L | 1221103-D28

1000L | 1221103-700

Application instructions

RAVENOL MTF-2 SAE 75W-80 is a full synthetic transmission oil for manual transmissions.

Characteristics

- A high-pressure stable lubricating film even at high oil temperatures and under high stress.
- Outstanding shearing stability and excellent thermal stability.
- Excellent viscosity-temperature properties.
- High oxidation stability.
- Excellent wear protection, outstanding EP properties.
- Low foaming property even at high speeds
- Good shifting behaviour even in low temperatures, extremely low pour point.
- Extended life.

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	9,1	DIN 51562-1
Viscosity at 40 °C	mm ² /s	50,8	DIN 51562-1
Viscosity Index VI		163	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	21.900	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m ³	847,5	EN ISO 12185
Flashpoint	°C	248	DIN EN ISO 2592
Pourpoint	°C	-51	DIN ISO 3016