



RAVENOL MTF-3 SAE 75W

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1221104

Viscosity: 75W

Specifications: API GL-4

Oil type: Full synthetic

Recommendations: AC Delco 10-4037, BMW 23007533818 MTF-LT-3, BMW 83220396706 MTF-LT-3, BMW 83227533818 MTF-LT-3, BOT 303, BOT 350 M3, Fiat 9.55550-MZ6, Ford MU7J 7J106 AA, Ford WSS-M2C200-D2, Ford WSS-M2C200-D3, Ford WSS-M2C200-E1, JWS 2271, MB 235.10, MB (A 001 989 84 03 09), Opel B0402167, PSA 9730A8, PSA B71 2310, PSA B71 2316, PSA B71 2317, Suzuki 99000-22B27-036, Toyota 08885-81001, Toyota 08885-81081, VW G 009 317 A2, VW G 052 171 A2, VW G 052 512 A2, VW G 052 527 A2, VW G 055 512 A2, VW G 055 532 A2, VW G 070 726 A2, VW G F53 061 M2, VW/Audi G 060 726 A2

Application: Passenger car



RAVENOL MTF-3 SAE 75W is a full synthetic low-viscosity transmission oil for special manual transmissions.

RAVENOL MTF-3 SAE 75W is designed based on special selected base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

RAVENOL MTF-3 SAE 75W is outstanding for use under severe mechanical and thermal stress on transmission oils, even with extended oil change intervals.

Application instructions

RAVENOL MTF-3 SAE 75W is a full synthetic transmission oil for manual transmissions.

Characteristics

- A high pressure stable lubricating film even at high oil temperatures and under high stress.
- Outstanding shearing stability and excellent thermal stability.
- Excellent viscosity-temperature properties.
- High oxidation stability.
- Excellent wear protection, outstanding EP properties.
- Low foaming properties even at high speeds.
- Good shifting behaviour even in low temperatures, extremely low pour point.
- Extended life.
- A stable lubricating film even at high oil temperatures and under high stress.

1L | 1221104-001

4L | 1221104-004

10L | 1221104-010

20L | 1221104-020

20L | 1221104-B20

60L | 1221104-060

60L | 1221104-D60

208L | 1221104-208

208L | 1221104-D28

1000L | 1221104-700

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	7,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	35,1	DIN 51562-1
Viscosity Index VI		184	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	8.800	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m ³	840,0	EN ISO 12185
Flashpoint	°C	216	DIN EN ISO 2592
Pourpoint	°C	-48	DIN ISO 3016